



SMOKE EVACUATION FOR THE OFFICE AND SURGERY CENTER



MODERN DESIGN

A light-weight, ultra-quiet and compact design allowing for simplified operation and storage.

REDUCED RISK

The Smoke Shark II minimizing exposure to smoke plume during electrosurgical procedure increasing facility safety and reducing hazardous risk.

COST EFFECTIVE

The Extended-Life Filter (SF35) offers up to 35 hours performance reducing procedure cost by 38%(+/-) when used at the lowest setting.

INCREASED EFFICIENCY

Operates in conjunction with the optional Bovie Remote Activation Switch (SERS2) for maximized filter life and surgical efficiency.

RELIABLE

The Smoke Shark II Smoke Evacuator includes a standard two-year manufacturer warranty.

PROCEDURE SAFETY




Covered 3-port, 4-phase, filter design provides versatile accessory and procedure setup while decreasing risk of cross contamination.






STANDARD SETUP

| | | | |
|---|---|---|---|
| Long-Life 35-hr Filter | Pneumatic Footswitch | 6' non-sterile tube* | Arm Stand* |
|  |  |  |  |
| SF35 (included) | FSSEP (included) | 786T | SEAS |

* sold separately

Customize your Smoke Shark™ for a variety of applications by choosing from the accessories below...

| | | | | |
|---|---|--|---|---|
| 6' tube (sterile) | 6' tube with wand & tip (non sterile) | 6' tube with wand & tip (sterile) | Reducer fitting | Reducer fitting, sterile |
|  |  |  |  |  |
| 786TS | SETW | SETWS | SERF | SERFS |

| | | | | |
|--|--|---|--|---|
| Laparoscopic tubing kit (sterile) | Laparoscopic tubing kit with valve (sterile) | 6' tubing for ValleyLab® & IEC Pencil (sterile) | Laser-resistant wand (non-sterile) | Laser-resistant wand (sterile) |
|  |  |  |  |  |
| SELKS | SELVS | SEVL | SELW | SELWS |

Additional Accessories

| | | | | |
|---|---|--|---|---|
| Wall plate to hold canister | Fluid collection canister | Laser mask | Canister ring holder | Remote switch activator |
|  |  |  |  |  |
| SEWP | SEFC | SELM | SERH | SERS2 |

Smoke Shark II Technical Specifications...

| Dimensions: | Line Voltage: | Line Frequency: | Noise Level, dBA: |
|---|--|-----------------|--------------------|
| Height 15.2 cm (6 in.) Width 27.9 cm (11 in.) Depth 39.4 cm (15.5 in.) Weight 4.3 kgs (10 lbs) | SE02: 100/120 VAC SE02-220: 240 VAC | 50 - 60 Hz | 55.0 dBA (Maximum) |
| Warranty: two (2) year | | | |

The Smoke Shark II meets U.S. and International Standards.

OTHER OPTIONAL ACCESSORIES

TECHNICAL SPECIFICATIONS

